

**IPTC 12485**

## **Imaging Improvement of Fractured and Faulted Basement through Controlled Beam Migration Examples from Diamond Field in Vietnam**

Nabil EIKady and Yen Chu Tan, PETRONAS; Rizal Bakar, PETRONAS Carigali Vietnam Ltd.; Ziqiang (Joe) Zhou, Pauline Khoo and Ann Tan, CGGVeritas

Copyright 2008, International Petroleum Technology Conference

This paper was prepared for presentation at the International Petroleum Technology Conference held in Kuala Lumpur, Malaysia, 3–5 December 2008.

This paper was selected for presentation by an IPTC Programme Committee following review of information contained in an abstract submitted by the author(s). Contents of the paper, as presented, have not been reviewed by the International Petroleum Technology Conference and are subject to correction by the author(s). The material, as presented, does not necessarily reflect any position of the International Petroleum Technology Conference, its officers, or members. Papers presented at IPTC are subject to publication review by Sponsor Society Committees of IPTC. Electronic reproduction, distribution, or storage of any part of this paper for commercial purposes without the written consent of the International Petroleum Technology Conference is prohibited. Permission to reproduce in print is restricted to an abstract of not more than 300 words; illustrations may not be copied. The abstract must contain conspicuous acknowledgment of where and by whom the paper was presented. Write Librarian, IPTC, P.O. Box 833836, Richardson, TX 75083-3836, U.S.A., fax +1-972-952-9435.

---

### **Abstract**

The accurate determination of the velocity distribution in the subsurface is the single most important part in the long sequence of processing steps. Those accurate tomographic velocity models demand a state-of-the-art migration algorithms to honor the details that are needed in imaging the relevant complex structures. Controlled Beam Migration (CBM) is one of those techniques that exhibit an excellent impact on imaging Fractured and Faulted Granite basement. The velocity model that is used for depth imaging generally undergoes various iterations. It is the most difficult process, but yet also is the most important part of the velocity puzzle. Cell Based Tomography technique based on residual curvature analysis (RCA) was used for sediments velocity model building above the basement. In order to overcome the limitation of RCA tomography as it becomes less sensitive to velocity perturbation at deeper depth, Stack Sweep method has been performed to update the velocities inside the basement reservoir. This paper will concentrate mainly on the uplift of data imaging starting with Kirchhoff Pre Stack Time Migration passing through Kirchhoff Pre Stack Depth Migration and ending with Controlled Beam migration. CBM has a combined advantage of Kirchhoff migration (steep dip imaging) and Wave Equation Migration (multi-arrivals). It handles multi-arrivals, resulting in a cleaner image than Kirchhoff migration, and preserves the steep dips. Examples of the techniques are shown on data from Diamond Field, Offshore Vietnam with a discussion of specific issues that were encountered during processing.